

# 4x4overlander Instructions

## Nakatanenga Roof Tent Mounting System

### Fitting Guidelines



The Nakatanenga Roof Tent Mounting System will fit with a wide variety of roof tents and bars. However it is up to the purchaser to ascertain the suitability of this mounting system for their combination of tent and roof rack/bars.

The system consists of two mating square stainless steel frames. The black frame is bolted to the roof rack/bars and the natural stainless frame to the base of the roof tent.

- Select a suitable position on the base of the roof tent, normally centrally located.
- Then carefully mark and drill two 6mm clearance holes in the base of the roof tent in diagonally opposite corners.
- Fix frame to the base of tent then drill further 6mm clearance holes using the frame as a template.
- Ensure you have removed the mattress and are not near any wiring or struts etc before drilling.
- If your roof tent has a honeycomb floor structure, do not over tighten the bolts. Use the larger washers provided inside the roof tent.
- Position the black frame onto the roof bars/rack in a suitable location. If need be, adjust the spacing of the roof bars. If you have the CargoBear system, use the long T nuts, otherwise drill the roof bars for the bolts provided.
- Lift the tent into position and fasten the two frames together.

Please use the paste provided to prevent galling of the stainless nuts and bolts.



## Contact

For more information on this or any other product, please contact Brendan on 01422 243966 or 07929 604668